


DASH, DOOR, etc. For the soundproof and anti-vibration products of degreased coated surfaces


Product overview

Shinsung's 3060 product line is based on ASPHALT. It is used for the degreased coated surface such as DASH, DOOR of automobile and main purpose of soundproofing and dustproofing of steel sheet. It is TYPE treated with pressure-sensitive adhesive.

Product Model



Product Model



Product Category

PSN	Type
3061	Linear type
3062	Specific shape type

Technical Data

* Appearance	Solid
* Color	Black
* Specific Gravity	1.50 ~ 1.75
* Shrinkage Ration(%)	< 2.0%
* Adhesion	Before Curing > 0.25 kg/cm ²
Strength	After Curing > 0.60 kg/cm ²
	Water resistance > 0.60 kg/cm ²
* Operating Temperature	150~160°C, 30min

Application Method

1. Remove the release paper from the product and attach it to the desired location
2. If there is excessive rust preventive oil or dust on the attachment position, it is recommended to apply it after removing it cleanly.

Storage method (storage conditions)

1. Storage temperature Below 30°C
2. Validity 90 days from date of manufacture
3. This product contains many chemical materials. When exposed to direct sunlight and high temperature for a long time, deterioration of physical properties. Therefore, it should be stored away from heat sources and direct sunlight. In addition, thorough first-in-first-out is required depending on the storage period.

Additional Information

All of the above information is based on our knowledge and experience. we recommend to carry out sufficient reviews with us about using beyond technical purpose.